



We help ideas meet the real world



Retrosign GR1

Specifications

Optical specifications GR1 ASTM

Geometry:	ASTM-E-1709
- Entrance angle	-4°
- Observation angle	0.2°
- Light source angular aperture:	0.1°
- Receiver angular aperture:	0.1°
- Field of measurement, Ø	30 mm/1.2 inch and 15 mm /0.6 inch
Spectral responsivity:	
Illuminant A and V(λ) efficiency according to ASTM E1709 section 6.4.2. for selected filters.	
Range (cd·lx ⁻¹ ·m ⁻²):	0 – 2000

Optical specifications GR1 CEN

Geometry:	EN 12899
- Entrance angle	+5°
- Observation angle	0.33°
- Light source angular aperture:	0.16°
- Receiver angular aperture:	0.16°
- Field of measurement, Ø	30 mm/1.2 inch and 15 mm /0.6 inch
Spectral responsivity:	
Illuminant A and V(λ) efficiency according to ASTM E1709 section 6.4.2. for selected filters.	
Range (cd·lx ⁻¹ ·m ⁻²):	0 – 2000

Optical specifications GR1 Safety

Special version for safety clothing:

Geometry:	EN471
- Entrance angle	5°
- Observation angle	0.2°
- Light source angular aperture:	0.16°
- Receiver angular aperture:	0.16°
- Field of measurement, Ø	30 mm/1.2 inch / 15 mm /0.6 inch
Spectral responsivity:	
Illuminant A and V(λ) efficiency according to ASTM E1709 section 6.4.2. for selected filters.	
Range (cd·lx ⁻¹ ·m ⁻²):	0 – 2000

Instrument dimensions

Length:	295 mm / 11.6 inch
Width:	83 mm / 3.3 inch
Height:	324 mm / 12.8 inch
Weight:	2.1 kg / 4.6 lbs

Compliance

EMC:	EN 61326 : 2007
Low voltage:	Not applicable, battery driven

ROHS: Compliance to the requirement of and its exception. Directive 2002/95/EC; 2002/96/EC Annex 1A

Electrical characteristics

Power supply:	Rechargeable and replaceable Nickel Metal Hydride 9.6 V
External charger:	
- main	230 V / 50 Hz
- optimal	110 V / 60 Hz
- charge time	approx. 15 minutes
Data memory:	> 250.000 measurements
Interface:	USB

Environmental specification

Temperature:	
- Operating	0°C to +50°C / 32°F to 122°F
- Storage	-15°C to +55°C / 5°F to 131°F
Humidity:	non condensing

Timing

Measurement time:	2 sec.
-------------------	--------

Standard delivery

- Carrying case
- Calibration standard
- Software Program
- Battery charger
- Ø15 aperture reducer
- Small supporting plate
- Lens cover
- Communication cable
- Quick guide
- User manual on CD/DVD

Options

- Extension Pole Kit, 1.5-2.7 m / 4.9-8.9 feet
- Extra battery
- Ø10 aperture
- Calibration certificate
- Calibration service
- Lens attachment for additional entrance angles of 30° and 40°
- Bluetooth
- RFID tag reader
- Barcode reader
- High precision GPS unit